

Characteristics	Luxury RigidCore Plank Floating Floor with IXPE Underlayment and Valinge 5G click system
Description	Plank Size 9.37" Wide x 60" Long (Registered & Embossed) Peral Cove, Distant Shore, Egmont Key and Glistening Sand Plank Size 7" Wide x 48" Long (Registered & Embossed) Sand Dollar, Cockle, Banded Olive and Coquina
Size / Thickness	7.5mm Total Thickness (5.5.0mm Core + 1.5mm IXPE + 0.5mm Wearlayer)
Quality	1st quality, natural color variation, free of structural defects
Installation	Click System - Floating
Warranty	Lifetime Residential Wear Warranty Lifetime Structural Warranty Limited Lifetime Waterproof Warranty 10 Year Limited Light Commercial Warranty
Wear Resistance (method A)	2100 cycles - Classification (Class 33)
Impact Resistance (Big Ball)	1800mm - Classification (Class 34)
Micro-scratch Resistance	MSR-A2; MSR-B1 - Classification (Class 34)
Castor Chair Resistance	25,000 cycles - Classification (34) No visible damage effects from furniture leg testing.
Approximate IIC Rating on 6" Thick Concrete Slab Floor (150 lbs/cu ft)	IIC: 52 - (IIC: 64 with drop ceiling) STC: 49 - (STC: 61 with drop ceiling)
Residual indentation (Big Ball impact)	0.02 - Classification (34)
Resistance to staining	No visible change with 10 minute duration of contact (Water, acetone, cleaning solution, coffee, sodium hydroxide (NaOH), hydrogen peroxide (H ₂ O ₂), shoe polish.
Peel Strenth ISO 24345:2006	Mean Value: MD 110 N/50mm; AMD 105 N/50mm
Fungi Resistance ASTM G21-15	Unlike Cork, this product shows zero "None" results for observed growth.
FloorScore®	SCS-FS-04026 2016.06.01 - 2017.05.31

Packaging

Content of Box	(7" x 48" - 28.37Sq.Ft./CtnS) & (9.055" x 60" - 30.14Sq.Ft./Ctn)
Content of Pallet	(50 cartons - 1,418.50 SF per pallette = 7" Profile) & (48 cartons - 1446.72 SF per pallette = 9.055" Profile)