

Technical Specifications

Characteristics

Luxury RigidCore Plank Floating Floor with IXPE Underlayment and 5G Superior click system

Description

Plank Size 7" Wide x 48" Long (Registered & Embossed}  
Plank Size 9.05" Wide x 60" Long (Registered & Embossed)

Size / Thickness

6.5mm Total Thickness (5.0mm Core+ 1.5mm IXPE + 0.5mm Wear layer)

Quality

1st quality, natural color variation, free of structural defects

Installation

Click System - Floating

Warranty

Lifetime Residential Wear Warranty  
Lifetime Structural Warranty  
Limited Lifetime Waterproof Warranty  
10 Year Limited Light Commercial Warranty

Wear Resistance (method A)

2100 cycles - Classification (Class 33)

Impact Resistance (Big Ball)

1800mm - Classification (Class 34)

Micro-scratch Resistance

MSR-A2; MSR-B1 - Classification (Class 34)

Castor Chair Resistance

25,000 cycles - Classification (34) No visible damage effects from furniture leg testing.

Approximate IIC Rating on6" Thick Concrete Slab Floor (150 lbs/cu ft)

IIC: 52 - (IIC: 64 with drop ceiling)  
STC:49 - (STC: 61 with drop ceiling)

Residual indentation (Big Ball impact)

0.02 - Classification (34)

Resistance to staining

No visible change with 10 minute duration of contact (Water, acetone, cleaning solution, coffee, sodium hydroxide (NaOH), hydrogen peroxide (H2O2), shoe polish.

Peel Strength ISO 24345:2006

Mean Value: MD 110 N/50mm; AMD 105 N/50mm

Fungi Resistance ASTM G21-15

Unlike Cork, this product shows zero "None" results for observed growth.

Content of Box

7" x 48"	28.37 sq. ft.	9.05" x 60"	30.14 sq. ft.
----------	---------------	-------------	---------------

Content of Pallet

7" x 48"	50 cartons. 2,157 lbs.	9.05" x 60"	48 cartons 2,199.84 lbs.
----------	---------------------------	-------------	-----------------------------