

**Collection:** Coastal

**Luxury Rigid Core Plank Floating Floor** with IXPE Underlayment and 5G Superior click system

**Description:**

Plank Size 7" Wide x 48" Long (Registered & Embossed)

Plank Size 9.055" Wide x 60" Long (Registered & Embossed)

**Size / Thickness:** 7.5mm Total Thickness (5.5.0mm Core + 1.5mm IXPE + 0.5mm Wearlayer)

**Wearlayer:** 0.5mm (20mil)

**Quality:** 1st quality, natural color variation, free of structural defects

**Installation:** Click System – Floating

**Warranty:** Lifetime Residential Wear Warranty

Lifetime Structural Warranty

Limited Lifetime Waterproof Warranty

10 Year Limited Light Commercial Warranty

**Wear Resistance (method A):** 2100 cycles – Classification (Class 33)

**Impact Resistance (Big Ball):** 1800mm – Classification (Class 34)

**Micro-scratch Resistance:** MSR-A2; MSR-B1 – Classification (Class 34)

**Castor Chair Resistance:** 25,000 cycles – Classification (34) No visible damage effects from furniture leg testing.

**Approximate IIC Rating on 6" Thick Concrete Slab Floor (150 lbs/cu ft):** IIC: 52 – (IIC: 64 with drop ceiling)  
STC: 49 – (STC: 61 with drop ceiling)

**Residual indentation (Big Ball impact):** 0.02 – Classification (34)

**Resistance to staining:** No visible change with 10 minute duration of contact (Water, acetone, cleaning solution, coffee, sodium hydroxide(NaOH), hydrogen peroxide (H2O2), shoe polish.

**Peel Strength ISO 24345:2006:** Mean Value: MD 110 N/50mm; AMD 105 N/50mm

**Fungi Resistance ASTM G21-15:** Unlike Cork, this product shows zero "None" results for observed growth.

**FloorScore®:** SCS-FS-04026 | 2016.06.01 – 2017.05.31

## Packaging

**Content of Box:** (7" x 48" – 28.37Sq.Ft./CtnS) & (9.055" x 60" – 30.14Sq.Ft./Ctn)

**Content of Pallet:** (50 cartons – 1,418.50 SF per pallet = 7" Profile) & (48 cartons – 1446.72 SF per pallet = 9.055" Profile)

## Product:



Banded Olive



Cockel



Coquina



Distant Shore



Egmont Key



Glistening Sand



Pearl Cove



Sand Dollar